

NEW ARIAVE ELECTRICAL MATERIAL

We importing from big to small Distribution Board by fear price



SUPPLY INCLUDE

Frame

Front door with Reinforcing frame, 4 hinges and a points lock system

Rear panel

Top cover

mounting plate & 4 mounting plate supports

4 Lifting eyebolts

Removable cable gland plate

Paint finish

epoxy polyester powder coating textured finish profile: 9-fold profile

Material: cold rolling steel

Front door: 2.0mm

Rear panel: 1.5mm

Mounting plate: zinc coated 2.5mm

Protection degree: IP55

Color

RAL 7032 RAL 7035



CHARACTERISTICS

STRUCTURE

- Rails are made up of unique closed profile manufactured from 15/10 AISI 304L stainless steel.
- The frame corners are manufactured with orthogonal joints in AISI 304L stainless steel, laser welded to the rails.
- Only 8 high resistance screws in stainless steel are necessary to mount the structure, while two position pins allow the easy mounting of the two parts of the joint.
- Doors manufactured from 20/10 AISI 304L (AISI 316L on request) satin stainless steel with tubular stiffening frame.
- Hinges are made in zinc alloy, chrome plated, open 180° (hinges manufactured from AISI 316L stainless steel on request).
- Rear panel manufactured from 15/10 AISI 304L (AISI 316L on request) satin stainless steel.
- Roof manufactured from 15/10 AISI 304L (AISI 316L on request) satin stainless steel.
- Bottom manufactured from 15/10 AISI 304L (AISI 316L on request) satin stainless steel.

DELIVERY

- Structure
- door complete with MSB21-X locking system
- rear panel

